

AU2 Hood

For extraction of exhaust gasses.

The Geovent AU2 hood for extraction of exhaust gasses in combination with measurement of the engine on roll field etc. where there are a demand for extraction of big air volumes (up to 2000 m³/h). The hoods advantage versus a regular nozzle, is that it has no influence on the test result. The hood is fixed with a waste tray and includes a height adjustable stand.

3

Effective spot extraction

Geovent AU2 hood in $\varnothing 150$ and $\varnothing 200$ mm



Connection piece	$\varnothing 150$ & $\varnothing 200$ mm
Height, stand	500 mm height adjustable (special heights upon request)
Hood	Epoxy painted steel
Stand	Electro galvanised steel
Rec. air flow	$\varnothing 150$ = 800-1200m ³ /h $\varnothing 200$ = 1000-2000m ³ /h

Ordering tabel for AU2 hood

Art.no.	Model
07-035	AU2 hood $\varnothing 150$ mm with hight adjustable stand
07-040	AU2 hood $\varnothing 200$ mm with hight adjustable stand



GEOVENT

Hovedgaden 86
DK-8831 Løgstrup
Phone: (+45) 86 64 22 11
Telefax: (+45) 86 64 30 75
email: salg@geovent.dk
www.geovent.com



Juni 2001